





ITEM	T1	T2
LED backlight	9.4	14.2
EL / without backlight	4.6	10.0



FEATURE

1. 5X8 dots with cursor
2. Built- in controller (SPLC780D or Equivalent)
3. +5V power supply (Also available for +3.0V)
4. 1/16 duty cycle
5. BKL to be driven by pin1, pin2, or pin15, pin16 or A,K
6. N.V. Optional

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN	MAX	UNIT
POWER SUPPLY (LOGIC)	Vdd	-0.3	7.0	V
POWER SUPPLY (LCD)	V0	Vdd -13.5	Vdd +0.3	V
INPUT VOLTAGE	Vin	-0.3	Vdd +0.3	V

PIN ASSIGNMENT

PIN	SYMBOL	FUNCTION
1	Vss	GND
2	Vdd	Power Supply
3	V0	Contrast Adjust
4	RS	Register Select Signal
5	R/W	Data Read/Write
6	E	Enable Signal
7-14	DB0-DB7	Data Bus Line
15(A)	LED+	Power supply for BKL(+)
16(K)	LED-	Power supply for BKL(-)

MECHANICAL SPECIFICATIONS

CHARACTER NUMBER	20W X 2H	—
OVERALL SIZE	146.00W X 43.00H	mm
VIEWING AREA	123.00W X 23.00H	mm
HOLE - HOLE	139.00W X 36.00H	mm
CHARACTER SIZE	4.84W X 9.22H	mm
CHARACTER PITCH	1.16W X 0.53H	mm
DOT SIZE	0.92W X 1.10H	mm
DOT PITCH	0.06W X 0.06H	mm

ELECTRONICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	STANDARD			UNIT
			MIN	TYP	MAX	
Input voltage	V _{DD}	+5V	4.7	5.0	5.5	V
		+3.3V	2.7	3.0	3.3	V
Supply current	I _{DD}	V _{DD} =5V	---	2.5	4.0	mA
Recommended LCD driving voltage for normal temp version module	V _{DD-V0}	0 °C	4.7	4.8	5.5	V
		25 °C	4.3	4.5	4.7	
		50 °C	4.1	4.4	4.5	
LED forward voltage	V _F	25 °C	---	4.2	4.6	V
LED forward current	I _F	25 °C	---	300	---	mA
EL power supply current	EL	AC 400Hz V _{EL} =110V	----	---	---	mA

DISPLAY CHARACTER ADDRESS CODE

[illegible]